

Light Reflectivity

Heterogeneous Sheet

Concepts of Landscape™

All light reflectivity values listed are based on a percentage system, the higher the percentage (e.g., 20-24, 35-39), the higher the light reflectance of the floor. It is measured per ASTM E1349, Standard Test Method for Reflectance Factor and Color by Spectrophotometry Using Bidirectional (45°: 0° or 0°: 45°) Geometry. Research indicates reflectance can help drive daylight further into space and reduce reliance on artificial lighting, resulting in reduced electricity usage and costs. Glare from flooring is a characteristic of glossy finishes, not reflectance. Flooring in lighter colors with a matte finish have high reflectance values, but do not add to glare. Flooring with light reflectivity values greater than 25% can contribute to LEED® Interior Lighting Credit.

Value	SKUs
0-9	1HE2M006, 1HE2M011
10-14	1HE2M408, 1HE2M412, 1HE2M416
15-19	1HE2M008, 1HE2M009, 1HE2M010, 1HE2M016, 1HE2M420
20-24	1HE2M003, 1HE2M004, 1HE2M005, 1HE2M007, 1HE2M404, 1HE2M415
25-29	1HE2M015, 1HE2M402, 1HE2M407, 1HE2M411, 1HE2M419
30-34	1HE2M001, 1HE2M002
35-39	1HE2M014, 1HE2M418
40-44	1HE2M403, 1HE2M406, 1HE2M410, 1HE2M414
45-49	1HE2M013, 1HE2M409
50-54	1HE2M401, 1HE2M405, 1HE2M413, 1HE2M417
55-59	
60-64	
65-69	
70-74	

AHFContract.com

for complete Product, Technical, Adhesives, Installation, and Maintenance recommendations.

LEED® is a registered trademark of the United States Green Building Council. © 2025, AHF, LLC | All trademarks are owned by AHF, LLC, or its subsidiaries or affiliates.