

## Light Reflectivity

### Homogeneous Sheet

#### ***Mixed & Variegated™***

All light reflectivity values listed are based on a percentage system, the higher the percentage (e.g., 20-24, 35-39), the higher the light reflectance of the floor. It is measured per ASTM E1349, *Standard Test Method for Reflectance Factor and Color by Spectrophotometry Using Bidirectional (45°: 0° or 0°: 45°) Geometry*. Research indicates reflectance can help drive daylight further into space and reduce reliance on artificial lighting, resulting in reduced electricity usage and costs. Glare from flooring is a characteristic of glossy finishes, not reflectance. Flooring in lighter colors with a matte finish have high reflectance values, but do not add to glare. Flooring with light reflectivity values greater than 25% can contribute to LEED® Interior Lighting Credit.

Value	SKUs
0-9	1HG2M006, 1HG2M009
10-14	--
15-19	--
20-24	--
25-29	1HG2M005, 1HG2M018
30-34	1HG2M016, 1HG2M019
35-39	1HG2M004, 1HG2M008
40-44	--
45-49	1HG2M015, 1HGM017
50-54	1HG2M007, 1HG2M010, 1HG2M012
55-59	--
60-64	1HG2M013
65-69	1HG2M002, 1HG2M003, 1HG2M014
70-80	1HG2M001, 1HG2M011

#### **AHFContract.com**

for complete Product, Technical, Adhesives, Installation, and Maintenance recommendations.

LEED® is a registered trademark of the United States Green Building Council.

©2025, AHF, LLC | All trademarks are owned by AHF, LLC, or its subsidiaries or affiliates.